

EPO BLACK HOT MOUNTING MATERIAL

Optimize your mounting process with the new EPO BLACK

QPREP EPO BLACK is a fine granular, epoxy resin based thermosetting hot mounting material.

PRODUCT ADVANTAGES

- I Very low gap formation
- I High edge retention and plane parallelism
- I Low-dust, easy cleaning and no ram adhesion
- I No labelling required
- I High content of mineral filler
- I Hardness (Shore D): 93
- I Removal rate: Very low

RECOMMENDED APPLICATIONS

- I Routine applications
- I Edge examination
- I Mounting of medium-hard to hard materials



WHAT HAS CHANGED?

QATM offers a newly formulated hot mounting resin, and is pleased to introduce it's new product.

WHAT IS THE NEW?

- No need for labeling significantly improving occupational safety
- I Low-dust
- No adhesion to hot press ram (no need for antistick agents).

WHAT DO YOU NEED TO KNOW?

To achieve the best mounting results, adjust your process times and add 45-60 seconds to your previous heating cycle.





MATERIALOGRAPHIC SOLUTIONS ON DEMAND!

Whether you are an engineer, researcher, or involved in quality control, our website is packed with valuable information around materialographic products, consumables & applications.









START EXPLORING!



www.qatm.com

ATM QNESS GmbH · Emil-Reinert-Str. 2 · 57636 Mammelzen Tel. +49 2681 9539-0 · info@gatm.com · www.gatm.com

part of **VERDER** scientific